



US009557845B2

(12) **United States Patent**
Shahparnia

(10) **Patent No.:** **US 9,557,845 B2**
(45) **Date of Patent:** **Jan. 31, 2017**

(54) **INPUT DEVICE FOR AND METHOD OF COMMUNICATION WITH CAPACITIVE DEVICES THROUGH FREQUENCY VARIATION**

4,289,927 A 9/1981 Rodgers
4,320,292 A 3/1982 Oikawa et al.
4,334,219 A 6/1982 Paulus et al.
4,345,248 A 8/1982 Togashi et al.
4,405,921 A 9/1983 Mukaiyama
(Continued)

(75) Inventor: **Shahrooz Shahparnia**, Campbell, CA (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

CN 1243282 A 2/2000
CN 1278348 A 12/2000

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **13/560,958**

Haines, L. (Mar. 23, 2005). "Japanese Enable Human Area Network," *The Register* located at http://www.theregister.co.uk/2005/03/23/human_area_network/print.html, last visited Jun. 30, 2009, two pages.

(22) Filed: **Jul. 27, 2012**

(65) **Prior Publication Data**

US 2014/0028576 A1 Jan. 30, 2014

(Continued)

(51) **Int. Cl.**

G06F 3/041 (2006.01)
G06F 3/033 (2013.01)
G06F 3/044 (2006.01)
G06F 3/0354 (2013.01)

Primary Examiner — Srilakshmi K Kumar

Assistant Examiner — Stephen T Reed

(74) *Attorney, Agent, or Firm* — Morrison & Foerster LLP

(52) **U.S. Cl.**

CPC **G06F 3/0416** (2013.01); **G06F 3/033** (2013.01); **G06F 3/03545** (2013.01); **G06F 3/044** (2013.01)

(57)

ABSTRACT

A computing device configured to receive data from a peripheral device, such as a stylus. The computing device includes a processor, a touch interface, such as a touch screen, in communication with the processor and configured to detect an input corresponding to an object approaching or contacting a surface. The computing device further includes a touch filter in communication with the touch interface and a peripheral filter in communication with the touch interface. The touch filter is configured to reject a peripheral frequency corresponding to a peripheral signal of the peripheral device and the peripheral filter is configured to reject a touch frequency component corresponding to a touch signal corresponding to a touch input.

(58) **Field of Classification Search**

None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,462,692 A 8/1969 Bartlett
3,970,846 A 7/1976 Schofield et al.
4,220,815 A 9/1980 Gibson et al.
4,281,407 A 7/1981 Tosima

15 Claims, 9 Drawing Sheets

